



22 GAUGE MOVEMENT CONTROL WIRE, ON CENTER FOR IMPLUSE-DRIVE CLOCKS

|                          | 24"    | 30"    | 36"    | 42"    |
|--------------------------|--------|--------|--------|--------|
| CASE DIAMETER (A)        | 2'     | 2'-6"  | 3'     | 3'-6"  |
| CLOCK OPENING (B)        | 1'-9"  | 2'-3"  | 2'-9"  | 3'-3"  |
| MOUNTING FLANGE DIA. (C) | 2'-3"  | 2'-9"  | 3'-3"  | 3'-9"  |
| BEZEL DEPTH (D)          | 2 3/4" | 2 3/4" | 2 3/4" | 2 3/4" |
| CASE DEPTH (E)           | 5"     | 5"     | 5"     | 5"     |

DRAWING: SURFACE / SEMI-FLUSH MOUNT CLOCK 24"-42" DIA.  
 DESCRIPTION: TYPICAL SURFACE MOUNT CLOCK WITH OPTIONAL FLUSH MOUNT  
 DATE DRAWN: 1/16/2011 SCALE: VARIES

# LUMICHRON

CLOCKS WORLDWIDE

GRAND RAPIDS MI USA  
PHONE: 616.245.8888

WWW.LUMICHRON.COM